APPLICATION FOR PERMIT

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Dat	ate of filing in State Engineer's Office	APR 1 5 1985	
Ret	eturned to applicant for correction	·	
Cor	orrected application filed		
Maj	ap filed	APR 1 5 1985	under 48985
			<u>ifornia</u>
	P.O. Box 10628 Street and No. or P.O. Box No.	, of	Reno City or Town
	Nevada 89801 State and Zip Code No.	hereby make applica	tion for permission to appropriate the public
wate	aters of the State of Nevada, as hereinafter state	ed. (If applicant is a co	orporation, give date and place of incorpora-
tion	on; if a copartnership or association, give names	of members.)	
	California Corporation, Novem	ber 6, 1877	
լ1.	. The source of the proposed appropriation is.	Name of stream	Nood Gulch Well No. 6
2.			second-feet s 448.83 gals. per min.
	(a) If stored in reservoir give number of acre	-feet	
3.	. The water to be used for	Mining & Mill	ling lomestic, or other use. Must limit to one use.
4.			
	(a) Irrigation, state number of acres to be irri	igated	
	(b) Stockwater, state number and kinds of ar	nimals to be watered	
	(c) Other use (describe fully under "No. 12. I	Remarks"	
	(d) Power:		
	(1) Horsepower developed		
	(2) Point of return of water to stream		
5.	R 53 E, MDB &M., at a point fr survey, and by course and distance to a section corner. If	om which the East	Describe as being within a 40-acre subdivision of public to the corner of said Section 25 be so stated.
6.		egal subdivision. If on unsurvey	ection 25, T 44 N, R 53 E, MDB&M. ed land, it should be so stated.
7.	. Use will begin about January 1 Month and Day	and end about Dec	cember 31 , of each year.
8.	. Description of proposed works. (Under the p	provisions of NRS 535.0	010 you may be required to submit plans and
π.	specifications of your diversion or storage wo		
	used for exploration drilling flumes, drilled well with pump and motor, etc.		
9.	Estimated cost of works \$20	,000	

10 Esti	mated time required to con-	CITIICI WATER	5 Jears
IO. LUC	maiod anto roquiros to con	BLI GOL WOLKS	3 years If well completed, describe works.
11. Esti	mated time required to com	plete the application	of water to beneficial use 5 years
12. Rem	_		atering, state number and type of units to be served or annu-
	The annual consumpt	ive use is 235,	333,333 gallons per year. If the
	exploration drillin	ıg <u>proves out an</u>	ore body, then this water would be
	used for mining and	l milling of the	e ore body.
			By s/Alan S. Boyack ALAN S. BOYACK, AGENT
Compare	d <u>11</u> jf	js/bc	515 South Fifth Street
Protested			Elko, NV 89801
110105100			
	*********	APPROVAL	OF STATE ENGINEER
amount water r actual	of water herein gra right obtained under	anted is only a r this permit wi	xisting rights. It is understood that the temporary allowance and that the final ill be dependent upon the amount of water also understood that this right must allow
with a valve m install accurat meter m of Work Th public, No feet.	two (2) inch opening two (2) inch opening must be installed and maintained ince measurements must must be installed bear is filed. This Permit does not a perforations shall	ng for measuring nd maintained to in the discharge t be kept of wat efore any use of extend the perm ate lands.	water level. This well shall be equipped g depth to water. If the well is flowing, a prevent waste. A totalizing meter must be pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complemente the right of ingress and egress on production casing from ground level to 100
with a valve minstall accurate meter mof Work The public, No feet.	two (2) inch opening two (2) inch opening two two installed are led and maintained if the measurements must be installed be a is filed. The permit does not perforations shall will on PAGE 2) and of water to be appropriate the control of the contr	ng for measuring of maintained to in the discharge to be kept of watefore any use of extend the permate lands. I be put in the charted shall be limited shall be limited.	water level. This well shall be equipped g depth to water. If the well is flowing, a prevent waste. A totalizing meter must be epipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complemittee the right of ingress and egress on production casing from ground level to 100 d to the amount which can be applied to beneficial use, and
with a valve minstall accurate meter mof Work The public, No feet. (CONTINT The amount to exceed the control of the control o	two (2) inch openir must be installed ar led and maintained i te measurements must must be installed be t is filed. mis Permit does not private or corpora o perforations shall MUED ON PAGE 2) unt of water to be appropri-	ng for measuring and maintained to in the discharge to be kept of watefore any use of extend the permate lands. I be put in the mated shall be limited to the limited the limited that the limit	water level. This well shall be equipped g depth to water. If the well is flowing, a prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complemente the right of ingress and egress on production casing from ground level to 100 d to the amount which can be applied to beneficial use, and cubic feet per second , but not to exceed 235.91
with a valve minstall accurate meter mof Work The public Modern Continuous The amount to exemple to exemple to exemple of the amount to exemple of	two (2) inch opening two two installed are led and maintained ince measurements must must be installed bear is filed. This Permit does not perforations shall will on PAGE 2) unt of water to be appropriated. The gallons annually.	ng for measuring of maintained to in the discharge to be kept of watefore any use of extend the permate lands. I be put in the riated shall be limited and the lands.	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depth to the amount which can be applied to beneficial use, and cubic feet per second , but not to exceed 235.91
with a valve minstall accurate meter mof Work munical meter mof Work munical meters. (CONTING The amount to exceed million work munical meters)	two (2) inch opening the two that it is the installed and maintained in the measurements must be installed between its filed. The permit does not the perforations shall with the installed between the perforations in perforations in perforations in the perforation of the perforation is appropriated. The permit does not the perforation is shall with the perforation of the perforation of the perforation in the perforation of the perforation is appropriated. The permit does not the perforation of the perforation in the perforation of the perforation in the perforation of the perforation in the perforation in the permit is appropriated by the perforation of the permit is appropriated by th	ng for measuring ond maintained to in the discharge to be kept of watefore any use of extend the permete lands. In the charted shall be limited and the lands are lands.	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depends on the total to the amount which can be applied to beneficial use, and cubic feet per second, but not to exceed 235.91 decompleted on or before. October 22, 1987
with a valve minstall accurate meter mof Work munical meter mof Work munical meters. (CONTINT The amount to exceed million work munical meters.)	two (2) inch opening the two that it is the installed and maintained in the measurements must be installed between its filed. The permit does not the perforations shall with the installed between the perforations in perforations in perforations in the perforation of the perforation is appropriated. The permit does not the perforation is shall with the perforation of the perforation of the perforation in the perforation of the perforation is appropriated. The permit does not the perforation of the perforation in the perforation of the perforation in the perforation of the perforation in the perforation in the permit is appropriated by the perforation of the permit is appropriated by th	ng for measuring ond maintained to in the discharge to be kept of watefore any use of extend the permete lands. In the charted shall be limited and the lands are lands.	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depth to the amount which can be applied to beneficial use, and cubic feet per second , but not to exceed 235.91
with a valve minstall accurate meter mof Work multiple of the control of the cont	two (2) inch opening two two installed are must be installed are measurements must be installed be a is filed. The permit does not be perforations shall with the permit of the perforations of the perforations of the perforations shall with the perforation of	ng for measuring and maintained to in the discharge to be kept of watefore any use of extend the permete lands. In the criated shall be limited and be compared and be filed on or before	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depends on the total to the amount which can be applied to beneficial use, and cubic feet per second, but not to exceed 235.91 decompleted on or before. October 22, 1987
with a valve minstall accurate meter mof Work Mr. (CONTINT The amount to exceed million Work mur.)	two (2) inch opening the two that it is the installed and maintained in the measurements must be installed between the installed between the installed between two permit does not an openion of perforations shall be two perforations annually. State of the prosecuted with reason completion of work shall be two of water to beneficial use the prosecuted with reason of water to be prosecuted with reason of water to beneficial use the prosecuted with reason of water to be prosec	ng for measuring and maintained to in the discharge to be kept of wate fore any use of extend the permate lands. I be put in the riated shall be limited and be filed on or before	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depends to the amount which can be applied to beneficial use, and cubic feet per second, but not to exceed 235.91 depends on the completed on or before. October 22, 1987 November 22, 1987
with a valve minstall accurate meter mof Work The public, Not feet. (CONTINT The amount to exemple a million of the control o	two (2) inch opening must be installed and maintained in the measurements must must be installed be a is filed. The permit does not a perforations shall with the installed be a perforation of water to be appropriated. The prosecuted with reason completion of work shall be application of water to be application.	ng for measuring of maintained to in the discharge to be kept of watefore any use of extend the permate lands. It is put in the ciated shall be limited and be filed on or before	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depends on the amount which can be applied to beneficial use, and cubic feet per second , but not to exceed 235.91 depends on the completed on or before. October 22, 1987 November 22, 1989
with a valve minstall accurate meter mof Work The public Meter. (CONTINT The amount to exemple of a continuous million work muse the publication of the exemple of the map in such as a continuous million work muse the proof of the map in such as a continuous million work muse the proof of the map in such as a continuous million work muse the proof of the map in such as a continuous management of the map in such as a continuous management of the map in such as a continuous management of the map in such as a continuous management of the management	two (2) inch opening must be installed and maintained in the measurements must must be installed be a is filed. The permit does not a perforations shall with the installed be a perforation of water to be appropriated. The prosecuted with reason completion of work shall be application of water to be application.	ng for measuring and maintained to in the discharge to be kept of wate efore any use of extend the permete lands. In the limited of the put in the company of the permete shall be limited to the filed on or beneficial use shall be all use shall be filed on the limited to the shall be filed on the limited that the shall be filed on the shall be filed on the limited that t	water level. This well shall be equipped g depth to water. If the well is flowing, be prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 depends on the amount which can be applied to beneficial use, and cubic feet per second . But not to exceed 235.91 depends on the completed on or before. October 22, 1987 November 22, 1989 e filed on or before. November 22, 1989
with a valve minstall accurate meter mof Work The public of the control of the co	two (2) inch opening the two (2) inch opening the must be installed and the must be installed be a is filed. The permit does not a perforation shall will only private or corporate of perforations shall will only provide the appropriate of water to be appropriated. The provided with reason completion of work shall be on of water to beneficial using the application of water to be appropriate application of water to be appropriated application of water to be application of water to be appropriated application of water to be application.	ng for measuring and maintained to in the discharge to be kept of wate fore any use of extend the permete lands. In the limited of the put in the make shall be limited and be filed on or before	water level. This well shall be equipped g depth to water. If the well is flowing, to prevent waste. A totalizing meter must be epipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 d to the amount which can be applied to beneficial use, and include feet per second. The but not to exceed 235.91 december 22, 1987 November 22, 1987 The before Cottober 22, 1989 The filed on or before November 22, 1989 The or before November 22, 1989 The Engineer of Nevada, have hereunto set my hand and the seal of the complete of Nevada, have hereunto set my hand and the seal of the control of the contr
with a valve minstall accurate meter mof Work The public, Not feet. (CONTINT The amount to excomillion Work multiple Proof of the Map in successful to the completion of the proof of the	two (2) inch opening two (2) inch opening must be installed and maintained in the measurements must be installed between installed between two permit does not an opening perforation of water to be appropriated. State of the prosecuted with reason completion of work shall be the application of water to be appropriated and of work filed.	ng for measuring and maintained to in the discharge to be kept of wate fore any use of extend the permete lands. In the limited of the put in the mable diligence and be filed on or before	water level. This well shall be equipped g depth to water. If the well is flowing, o prevent waste. A totalizing meter must be a pipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 d to the amount which can be applied to beneficial use, and cubic feet per second . but not to exceed 235.91 december 22, 1987 November 22, 1987 November 22, 1989 The before October 22, 1989 The before October 22, 1989 The or before November 22, 1989
with a valve minstall accurate meter mof Work The public, Not feet. (CONTINT The amount to excomillion Work multiple Proof of the Map in successful Completion Proof of be Cultural minstall accurate meters accurate minstall accurate minstall accurate minstall accurate minstall accurate minstall accurate minstall accurate meters accurate minstall accurate minstall accurate meters accurate minstall accurate meters accurate minstall accurate meters accurate meters accurate minstall accurate meters accurate meters accurate meters accurate minstall ac	two (2) inch opening two (2) inch opening two two two transled and maintained ince measurements must be installed between installed between two permit does not perforations shall with two perforations shall with the application of water to be appropriated. The prosecuted with reason completion of work shall be the application of water to beneficial use the application of water to be appropriated and of work filed.	ng for measuring and maintained to in the discharge to be kept of watefore any use of extend the permate lands. I be put in the ciated shall be limited and to be effect on or before	water level. This well shall be equipped g depth to water. If the well is flowing, to prevent waste. A totalizing meter must be epipeline near the point of diversion and ter placed to beneficial use. The totalizing water begins or before the Proof of Complementate the right of ingress and egress on production casing from ground level to 100 d to the amount which can be applied to beneficial use, and include feet per second. The but not to exceed 235.91 december 22, 1987 November 22, 1987 The before Cottober 22, 1989 The filed on or before November 22, 1989 The or before November 22, 1989 The Engineer of Nevada, have hereunto set my hand and the seal of the complete of Nevada, have hereunto set my hand and the seal of the control of the contr

(PERMIT TERMS CONTINUED)

The total combined duty of water under Permits 48985, 48986, 48987, 48988, 48989, 48990, 48991, 48992 and 48993 shall not exceed 303.38 million gallons annually.

The manner of use of water under this permit is by nature of its activity a temporary use and any application to change the manner of use granted under this permit will be subject to additional determination and evaluation with respect to the permanent effects on existing rights and the resource within the ground water basin.

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal and local agencies.

